

PHYSICAL DISTRIBUTION BUSINESS MANAGEMENT  
METHOD, PHYSICAL DISTRIBUTION BUSINESS  
MANAGEMENT SYSTEM, AND STORAGE MEDIUM

BACKGROUND OF THE INVENTION

5 Field of the Invention

The present invention relates to a physical distribution business management method for managing physical distribution business and a physical distribution business management system.

Description of the Related Art

10 In the case where a consignor transports (exports) goods to a consignee oversea, the consignor places goods in a shipping agency's keeping, the consignor or shipping agency conducts a customs procedure, the shipping agency or an agency that is under contract to this shipping agency transports goods to the consignee. In addition to  
15 the consignor and consignee, the number of parties, who are concerned with exporting goods, for example, the shipping agency, the customs, increases. This also increases the number of documents used in the procedure for the delivery of goods between the respective parties concerned. For this reason, the documents used in the procedure  
20 became complicated, and this made it difficult for the party concerned to grasp the progress of the procedure relating to the transport of goods.

SUMMARY OF THE INVENTION

The present invention has been made in view of the foregoing  
25 circumstances, and an object of the present invention is to provide a

10020932-121901

physical distribution business management method that makes it easier to grasp the progress of the procedure relating to the transport of goods, a physical distribution business management system, and a storage medium.

- 5 In order to attain the above object, according to a first aspect of the present invention, there is provided a physical distribution business management method comprising an image data generation step for generating image data of a document on which a condition for exporting or importing goods is described; an image data storage step  
10 for storing image data generated in the image data generation step to be associated with the goods; a document data storage step for storing document data described on the document to be associated with the goods; an identification data storage step for storing identification data that identifies a party concerned with export or import of said goods;  
15 and a data output step, when said party concerned specifies data relating to goods, for obtaining data of goods stored to be associated with the corresponding specified data in said stored data to output said obtained data, wherein the identification data storage step decides a range of an output enable data to the party concerned based on stored  
20 identification data, and the data output step obtains data matching the decided range.

The document data storage step may store date data representing an execution date of procedures for exporting or importing the goods to be associated with the goods, and the data output step may specify a  
25 completed procedure of the procedures based on the date data and

output data representing the corresponding specified procedure.

The data output step may display a diagram illustrating a correspondence between a person who conducts the specified procedure and a person who receives the procedure and outputs data  
5 representing the corresponding procedure.

The document data storage step may display image data stored in the image data storage step and store document data from the document displayed in the image data.

The image data generation step may read an image of the face of  
10 the document and generate the image data representing the read image, and the image data storage step may obtain the generated image data and store the obtained image data to be associated with the corresponding goods.

According to a second aspect of the present invention, there is  
15 provided a physical distribution business management system comprising image data generation means for generating image data of a document on which a condition for exporting or importing goods is described; image data storage means for storing image data generated by the image data generation means to be associated with the goods;  
20 document data storage means for storing document data described on the document to be associated with the goods; identification data storage means for storing identification data that identifies a party concerned with export or import of the goods; and data output means, when the party concerned specifies data relating to goods, for  
25 obtaining data of goods stored to be associated with the corresponding

specified data in the stored data to output the obtained data, wherein the identification data storage means decides a range of an output enable data to the party concerned based on stored identification data, and the data output means obtains data matching the decided range.

- 5       The document data storage means may store date data representing an execution date of procedures for exporting or importing the goods to be associated with the goods, and the data output means may specify a completed procedure of the procedures based on the date data and output data representing the corresponding
- 10   specified procedure.

      The data output means may display a diagram illustrating a correspondence between a person who conducts the specified procedure and a person who receives the procedure and output data representing the corresponding procedure.

- 15       The document data storage means may display image data stored by the image data storage means and store document data from the document displayed in the image data.

- The image data generation means may read an image of the face of the document and generate the image data representing the read
- 20   image, and the image data storage means may obtain the generated image data and store the obtained image data to be associated with the corresponding goods.

- According to a third aspect of the present invention, there is provided a computer-readable storage medium having a computer-
- 25   program recorded thereon, the computer program causing a computer

to perform functions of image data generation means for generating image data of a document on which a condition for exporting or importing goods is described; image data storage means for storing image data generated by the image data generation means to be  
5 associated with the goods; document data storage means for storing document data described on the document to be associated with the goods; identification data storage means for storing identification data that identifies a party concerned with export or import of the goods to decide a range of an output enable data to the party concerned based on  
10 stored identification data; and data output means, when the party concerned specifies data relating to goods, for obtaining data of goods, which is stored to be associated with the corresponding specified data in the stored data and which matches the decided range, to output the obtained data.

## 15 BRIEF DESCRIPTION OF THE DRAWINGS

These objects and other objects and advantages of the present invention will become more apparent upon reading of the following detailed description and the accompanying drawings in which:

FIG. 1 is a block diagram illustrating a structure of a freight  
20 tracking information management system according to an embodiment of the present invention;

FIG. 2 is a flowchart showing processing for document image registration;

FIG. 3 is a flowchart showing processing for database use;

25 FIG. 4 is a view schematically illustrating a login image;

FIG. 5 is a view schematically illustrating a selective image;

FIG. 6 is a view schematically illustrating an allocation  
information display image;

FIG. 7 is a view illustrating a status in which information relating  
5 to goods are transmitted to the parties concerned; and

FIG. 8 is a view schematically illustrating a stock display image.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The following will explain a physical distribution business  
10 management method, a physical distribution business management  
system and a storage medium according to an embodiment of the  
present invention taking a freight tracking information management  
system for grasping the status of transport of exported goods as an  
example.

15 FIG. 1 is a block diagram illustrating the structure of the freight  
tracking information management system according to the  
embodiment of the present invention. As illustrated in FIG. 1, the  
freight tracking information management system is composed of key  
business servers 1-1 to 1-m (m represents the sum total number of key  
20 business servers), key business terminals 2-1 to 2-m, a database  
management server 3, a database management terminal 4, and user  
terminals 5-1 to 5-n (n represents the sum total number of user  
terminals).

The key business servers 1-1 to 1-m are connected to the key  
25 business terminals 2-1 to 2-m via a LAN (Local Area Network) and

the like, respectively. The key business servers 1-1 to 1-m are connected to the database management server 3 via a private communications line and the like. The database management terminal 4 is connected to the database management server 3 via LAN and the like. The user terminals 5-1 to 5-n are connected to the database management server 3 via an external network such as the Internet.

The key business servers 1-1 to 1-m are composed of a server computer and the like, respectively. The key business servers 1-1 to 1-m obtain data supplied from the key business terminals 2 and execute processing for document image registration to be described later, respectively.

A scanner S is connected to at least any one of the key business servers 1-1 to 1-m. In this example, the scanner S is connected to a key business server 1-j (j represents an arbitrary integer, which is from one to m inclusive).

A PDF (Portable Document Format) output driver is stored in at least any one of the key business servers 1-1 to 1-m. The key business server that stores the PDF output driver executes the PDF output driver to generate image data described in a PDF format in processing for document image registration.

Such key business servers 1-1 to 1-m are placed at locations handling the exported goods or information relating to the exported goods. Then, the key business servers 1-1 to 1-m perform processing for information that is handled at the location where they are placed, respectively. Such locations include, for example, a production plant

for exported goods, a business center that manages a production schedule for exported goods, a physical distribution center that keeps the stock of exported goods, the customs, address of NVOCC (transportation company using overseas shipping) or a shipping company, a shipping port where exported goods are shipped, an unloading port where exported goods are unloaded, and address of the consignee.

It is assumed that the user of the freight tracking information management system signs a contract with a manager of the freight tracking information management system to handle FDF-formatted image data as being substantially identical with the original document indicated by the corresponding image data. Then, supposing that the manager of the freight tracking information management system operates based on the presence of this contract as a precondition.

Moreover, in the freight tracking information management system, security setting for protecting against tampering such as read-only setting and the like is provided to FDF-formatted image data that the freight tracking information management system generates.

The key business terminals 2-1 to 2-m comprises an input device composed of a keyboard and a mouse, and a personal computer having a display device composed of a liquid crystal display and the like. Then, information input by the operator of key business terminals 2-1 to 2-m using the input device is provided to the key business servers 1-1 to 1-m connected via LAN or the like.

The database management sever 3 is composed of a server



computer and the like. The database management server 3 executes processing for document image registration with the key business server 1-j and the key business terminal 2-j. Moreover, the database management sever 3 executes processing for database construction to  
 5 be described later with the database management terminal 4. Still moreover, the database management sever 3 executes processing for database use to be described later with the user terminal 5.

Still moreover, in the database management server 3, a freight tracking information database, a WWW (World Wide Web) server  
 10 program, and a CGI (Common Gate Interface) for managing database are stored.

The freight tracking information database is a database that registers information relating to the freight which this freight tracking information management system undertakes the transportation. More  
 15 specifically, in the freight tracking information database, for example, data indicated in the following (a) and (b) is stored to be associated with each other.

(a) Image data representing the faces of various kinds of documents relating to the freight; and

20 (b) Data described in the faces indicated by image data of (a);

The documents indicated by image data of (a) includes, for example, documents (a1) to (a15) given below:

(a1) Commercial Invoice;

(a2) Packing List

25 (a3) Goods Number List (List of identification number assigned

to goods)

(a4) B/L (Bill of Landing), Consignment Note

(a5) CLP (Container Load Plan)

(a6) CFM (Container Freight Manifest)

5 (a7) Container Stacking Plan

(a8) Various Document for Customs

(a9) P/O (Purchase Order)

(a10) S/O (Shipping Order)

(a11) S/I (Shipping Instructions)

10 (a12) D/O (Delivery Order)

(a13) E/L (Export License)

(a14) Stock List

(a15) Shipping Advice

These documents can be classified into documents for customs

15 ((a1), (a2), (a8)), overseas shipment documents ((a1) to (a6)),  
combined transport documents ((a4) to (a6)), and other shipping  
related document ((a7)).

Data of (b) includes, for example, documents (b1) to (b56)) given  
below:

20 (b1) Code for identifying P/O

(b2) Receipt date of P/O indicated by data of (b1)

(b3) Name of a person who orders goods using P/O indicated by  
data of (b1) (or designation or other data identifying the person)

(b4) Name of a person who bears the shipping cost of goods  
25 ordered using P/O indicated by data of (b1)

10020933-121901  
T06T2T-2E60200T

(b5) Code for identifying S/O that provides an order to ship goods ordered using P/O indicated by data of (b1)

(b6) Code for identifying S/I that provides instructions to ship goods ordered using P/O indicated by data of (b1)

5 (b7) Issue date of S/I indicated by data of (b6)

(b8) Name of a ship instructed to ship using S/I indicated by data (b6)

(b9) Data representing a shipping port for the ship instructed to ship using S/I indicated by data (b6)

10 (b10) Data representing an unloading port for the ship instructed to ship using S/I indicated by data (b6)

(b11) Unload date of goods instructed to ship using S/I indicated by data (b6)

(b12) Name of goods instructed to ship using S/I indicated by data  
15 (b6)

(b13) Supplier of goods indicated by data of (b12)

(b14) Quantity of ordered goods indicated by data of (b12)

(b15) Quantity of goods, indicated by data of (b12), planed to be manufactured

20 (b16) Quantity of manufactured goods indicated by data of (b12)

(b17) Quantity of shipped goods indicated by data of (b12)

(b18) Goods number assigned to goods indicated by data (b12)

(b19) EDP (Electronic Data Processing) code assigned to goods indicated by data (b12)

25 (b20) Code for identifying the commercial invoice of goods

10020932-121901

indicated by data (b12)

(b21) Contents of the commercial invoice indicated by data (b12)

(b22) Container number assigned to a container on which goods, indicated by data (b12), are loaded

5 (b23) Weight of the container indicated by data (b22)

(b24) Load factor of the contain indicated by data (b22)

(b25) Case number assigned to a case loaded on the container indicated by data (b22)

(b26) Weight of the case indicated by data (b25)

10 (b27) Load factor of the case indicated by data (b25)

(b28) Code for identifying B/L

(b29) Contents of B/L indicated by data of (b28)

(b30) Code for identifying Shipping Advice

(b31) Contents of Shipping Advice indicated by data of (b30)

15 (b32) Scheduled date for issuing D/O and issue date of D/O

(b33) Scheduled date for packing and date which packing was performed

(b34) Scheduled date for vaning (loading onto the container) and date which vaning was performed

20 (b35) Scheduled date for starting up to carry to the shipping port and start-up date of carrying

(b36) Scheduled date for ending to carry to the shipping port and end date of carrying

(b37) Scheduled date for starting up the customs procedure and  
25 start-up date of the customs procedure

10020932-121901

(b38) Scheduled date for receiving a resultant report of the customs procedure and date that the resultant report was received

(b39) Scheduled date for obtaining E/L and E/L obtaining date

(b40) Scheduled date for shipment work and shipment work

5 executing date

(b41) Scheduled date for sailing and sailing date

(b42) Scheduled date for arriving in port

(b43) Scheduled date for issuing B/L indicated by data of (b28) and issue date of B/L

10 (b44) Scheduled date for shipping B/L and the like and shipping date of B/L and the like

(b45) Addressee of goods ordered to ship by S/O indicated by data of (b5)

(b46) Carrier who carries goods ordered to ship by S/O indicated  
15 by data of (b5)

(b47) Name of goods ordered to ship by S/O indicated by data of (b5)

(b48) Supplier of goods indicated by data of (b47)

(b49) Quantity of ordered goods indicated by data of (b47)

20 (b50) Quantity of goods, indicated by data of (b47), planed to be manufactured

(b51) Quantity of manufactured goods indicated by data of (b47)

(b52) Quantity of shipped goods indicated by data of (b47)

(b53) Goods number assigned to goods indicated by data (b47)

25 (b54) EDP code of goods indicated by data (b47)

10020932-121901

(b55) Code for identifying the commercial invoice of goods indicated by data (b47)

(b56) Contents of the commercial invoice indicated by data (b47)

It should be noted that data of (b12) to (b20) might be used as data  
5 of (b47) to (b56).

Moreover, in the freight tracking information database, data indicated as (c1) to (c4) shown below is stored to be associated with one another.

(c1) User's name of the freight tracking information management  
10 system, address, and e-mail address

(c2) ID (Identification Code) assigned to the user indicated by data of (c1)

(c3) Password assigned to the user indicated by data of (c1)

(c4) Data indicating an authorization group to which the user  
15 indicated by data of (c1) belongs

Here, the authorization group indicated by data of (c4) can be classified into the following eight kinds (A) to (H).

(A) System manager (person who manages this freight tracking information management system)

20 (B) Operation manager (person who is authorized to gain access to data that this freight tracking information management system holds in conformity with the system manager)

(C) Export business user (person who is authorized to gain access to data other than the combined transport document)

25 (D) Combined transport business user (person who is authorized

10020932-121901  
106121-2662001

to gain access to data other than the overseas shipment document)

(E) Intra-company general user (person who is authorized to gain access to data excepting the combined transport document, customs document, and overseas shipment document)

5 (F) Consignor user (person, who is authorized to gain access to data relating to goods of which the user oneself is the consignee)

(G) Client user (person, who is authorized to gain access to data relating to goods of which the user oneself is the consignor)

(H) Combined transport cooperation company user (person who  
10 is authorized to gain access to data relating to the combined transport document)

Moreover, in the freight tracking information database, data indicated as (d1) to (d3) shown below is stored to be associated with one another.

15 (d1) Goods number to be exported and EDP code

(d2) Amount of change in the stock of goods indicated by data of (d1)

(d3) Day that the change in the stock indicated by data of (d2) occurred

20 The WWW server program is a program for causing the database management server 3 to perform processing of WWW server. When a URL (Uniform Resource Locator) indicating a logical location of data is supplied to the database management server 3, the database management server 3 that executes the WWW server program reads  
25 data, which is placed at the logical position indicated by this URL,

10020932-121901

from a storage area of storage that the database management server 3 has or the storage area where the database management server 3 is accessible, and sends back read data to the supply source of this URL.

The database management CGI is a program for causing the  
5 database management server 3 and user terminal 5 to perform processing for database use. When URL indicating the database management CGI is supplied to the database management server 3 from the user terminal 5, processing for database use is executed by the database management server 3 in accordance with control the  
10 WWW server program.

Furthermore, as illustrated in FIG. 1, the database management server 3 stores a PDF generation driver. The PDF generation driver converts image data, which is not in a PDF format, to PDF-formatted image data in processing for document screen page registration.

15 The database management terminal 4 comprises an information processing device of a personal computer having an input device composed of a keyboard and a mouse and a display device composed of a liquid crystal display and the like. Then, information input by the operator of the database management terminal 4 is provided to the  
20 database management server 3 connected via LAN and the like so as to execute processing for database construction.

The user terminal 5 comprises an information processing device of a personal computer having an input device composed of a keyboard and a mouse and a display device composed of a liquid  
25 crystal display and the like.



The user terminal 5, for example, user terminal 5-k (k represents an arbitrary integer, which is from one to n inclusive) executes processing for WWW browser. Namely, when the user inputs URL, the user terminal 5-k gains access to a device (for example, database management server 3) accessible to the logical position indicated by the corresponding URL and requests the device to transmit data being placed at the logical position indicated by the URL. Then, the user terminal 5-k receives data transmitted by this device in response to this request and displays an image shown by received data.

Then, the user terminal 5k executes processing for database management server 3 and database use when supplying URL for database management CGI to the database management server 3.

(Operation)

An explanation will be next given of an operation of this freight tracking information management system. In this example, the operation of freight tracking information management system will be explained according to processing for document image registration, processing for database construction and processing for database use.

(Processing for document image registration)

The processing for document image registration is processing that registers a document image to the freight tracking information database. FIG. 2 is a flowchart showing processing for document image registration.

In the physical distribution steps that constitute the procedure of export, the parties concerned with the procedure of export prepare or

receive a document relating to a physical distribution process as a result obtained by executing the physical distribution step with which each party is concerned (step S11 in FIG. 2). At this time, they register the image of this document (namely, the forgoing data of (a)) to this

5 freight tracking information management system.

More specifically, the operator, who is the party concerned with the procedure of export, sets this document to the scanner S connected to the key business server 1-j. Next, the operator operates the key business terminal 2-j and sends a command to the key business server

10 1-j so as to instruct the scanner S to scan an image. The key business server 1-j scans the image on the face of the document set to the scanner S connected to the key business server 1-j in response to this instruction and generates image data representing the read image (step S12).

15 The documents to be scanned by the scanner S are P/O and the like if the key business server 1-j to which the scanner S is connected is located at the production plant. Moreover, if it is located at the business center, the documents are, for example, commercial invoice, S/I and the like. If it is located at the physical distribution center, the

20 documents are, for example, packing list, goods number, stock list, and the like. If it is located at NVOCC or the shipping company, the documents, for example, S/O, B/L, or consignment note, D/O, and CLP. Moreover, if the key business server 1-j is located at the customs, the documents are, for example, E/L and various kinds of customs

25 documents. If it is located at the shipping port, the documents are, for

example, CFM, container stacking plan, and shipping advice.

The operator of key business terminal 2-j operates the input device of key business terminal 2-j and inputs data that specifies which one of the foregoing data of (a1) to (a15) this image data forms, so that  
5 the kind of document is specified. Resultantly, the key business terminal 2-j supplies data indicating the kind of image data specified by the operator to the key business server 1-j as data to be added to image data.

When image data indicating the image scanned by the scanner S  
10 and data indicating the kinds of image are supplied to the key business server 1-j from the key business terminal 2-j, the key business server 1-j adds data indicating the kind of image to image data and stores image data temporarily.

At this time, the operator can operate the input device of the key  
15 business terminal 2-j without scanning the image by use of scanner S. Namely, the operator can instruct the input device of the key business terminal 2-j to input data specifying the kind of document and description matters of the kind of document indicated by the corresponding data and generate image data indicating the image of  
20 the corresponding document in which the input description matters are described. In this case, the key business terminal 2-j generates image data that indicates the image of the corresponding document in which the description matters input by the operator is described in response to this instruction (step S12). The key business terminal 2-j adds data,  
25 which indicates the kind of document specified by the operator, to

image data generated based on the description matters input by the operator, and supplies it to the key business server 1-j. When the corresponding image data is supplied from the key business terminal 2-j, the key business server 1-j stores this image data temporarily.

5 In the case where the key business server 1-j stores the PDF output driver, the key business server 1-j executes the PDF output driver so as to convert image data temporarily stored by the processing for document image registration to data described in the PDF format. Then, the key business server 1-j supplies PDF-formatted image data  
10 to the database management server 3 in, for example, a fixed cycle (step S13).

On the other hand, in the case where the key business server 1-j does not store the PDF output driver, the key business server 1-j supplies image data temporarily stored to the database management  
15 server 3 (step S13).

When image data is supplied from the key business server 1-j, the database management server 3 stores this image data temporarily. Then, the database management server 3 gains access to the key business server 1-j and determines whether or not image data, which is  
20 temporarily stored by the database management server 3, substantially matches image data, which is temporarily stored by the key business server 1-j.

Then, when determining that both match each other, the database management server 3 stores image data temporarily stored to the  
25 freight tracking information database as data of (a) (step S14). Here, in

the case where the corresponding data is not one that is described in the PDF format, the database management server 3 executes the PDF generation driver so as to convert the corresponding image data, which is stored by the database management server 3, to data described in the PDF format. Then, the database management server 3 stores the PDF-formatted image data obtained by conversion to the freight tracking information database.

On the other hand, when determining that both do not match each other, the database management server 3 obtains one of data, which the key business server 1-j stores temporarily and which the database management server 3 does not temporarily store, from the key business server 1-j, and stores it temporarily. Thereafter, the database management server 3 stores image data temporarily stored by the server 3 to the freight tracking information database as data of (a) (step S14). Similarly, in this case, if the corresponding data is not one that is described in the PDF format, the database management server 3 executes the PDF generation driver so as to convert the corresponding image data, which is stored by the database management server 3, to data described in the PDF format. Then, the database management server 3 stores the PDF-formatted image data obtained by conversion to the freight tracking information database.

(Processing for database construction)

The processing for database construction is processing in which data (data of (b)), which is described on the face of the document indicated by data of (a), is registered to the freight tracking

information database having data of (a) registered by the processing for document image registration so as to construct the freight tracking information database.

First, the operator of the database management terminal 4

5 (manager of the freight tracking information system and the like) operates the input device of database management terminal 4 and instructs the input device of database management terminal 4 to specify data of (a) indicating the document to which data of (b) is not stored yet.

10 The database management terminal 4 gains access to the database management server 3 in response to this instruction. Then, the database management terminal 4 searches the freight tracking information database stored in the database management server 3 and specifies one of data of (a), which is stored in the freight tracking  
15 information database and which is not yet associated with other data. Then, the database management terminal 4 lists the names of specified data of (a) on the display screen page of the display device that the terminal 4 has.

Next, the operator of the database management terminal 4  
20 operates the database management terminal 4, inputs at least one of the names listed, and instructs the database management terminal 4 to display the image of the document indicated by data of (a) having the input name.

The database management terminal 4 gains access to the database  
25 management server 3 in response to this instruction, and reads one of

data of (a), which is stored in the freight tracking information database and which has the name input by the operator. Then, the database management terminal 4 displays the image indicating read data of (a).

Sequentially, the operator of the database management terminal 4  
5 inputs description matters that form any of data of (b1) to (b56) among the description matters as visually identifying the description matters included in the image of document displayed by the database management terminal 4. Then, the operator instructs the database management terminal 4 to store the input description matters to the  
10 freight tracking information database.

The database management terminal 4 stores these description matters input by the operator to the freight tracking information database as data of (b) in accordance with this instruction.

Additionally, the operator of the database management terminal 4  
15 may input data corresponding to any of data of (b1) to (b56) without displaying the image of document on the database management terminal 4. Similarly, in this case, when the operator instructs the database management terminal 4 to store the input description matters to the freight tracking information database, the operator instructs the  
20 database management terminal 4 stores these data input by the operator to the freight tracking information database as data of (b) in accordance with this instruction.

(Processing for database use)

The processing for database use is processing for grasping the  
25 progress of the procedure relating to the transport of freight by use of

10020932-121901  
T06T2T-2E6000T

the constructed freight tracking information database.

First, an explanation will be given of a user registration that is performed so that the user uses the freight tracking information database.

- 5       The user operates the input device of user terminal 5-k to display a user registration image (not shown) for performing the user registration on the display screen page of the display device that the user terminal 5k has. Next, the user inputs data of (c1) including user's name, address and e-mail address, and instructs the user terminal 5-k
- 10   to register it to the freight tracking information database as data of (c1). The user terminal 5-k supplies data of (c1) to the database management server 3.

- The database management server 3 registers supplied data to the freight tracking information database and assigns user ID (data of (c2))
- 15   and user password (data of (c3)) and supplies them to the user terminal 5-k. The user terminal 5-k displays supplied data of (c2) and data of (c3) on the display device that the user terminal 5-k has. Moreover, the database management server 3 registers data of (c4) of any one of the authorization groups to which the user belongs to the freight tracking
- 20   information database from data of (c1).

An explanation will be next given of the processing for database use.

- The user operates the input device of user terminal 5-k and inputs URL of the database management CGI. Then, the user instructs the
- 25   user terminal 5-k to gain access to the database management server 3.



When the user terminal 5-k gains access to the database management server 3, the database management server 3 executes the database management CGI. Resultantly, the database management server 3 and user terminal 5-k perform the processing for database use explained below. FIG. 3 is a flowchart showing processing for database use.

When the database management CGI is started up, the database management server 3 generates data indicating the login image for performing authentication of user and supplies it to the user terminal 5-k. In response to the fact that the database management server 3 has supplied this data, the user terminal 5-k displays the login image indicated by data supplied to the terminal 5-k on the display screen page of the display device that the terminal 5-k has.

The login image includes an ID entry field for entering a user ID, a password entry field for entering a user password, and a transmission button ("login") for instructing the supply of the entered ID and password to the database management server 3 as illustrated in FIG. 4.

Then, the user operates the input device of user terminal 5-k, inputs ID to the ID entry field and the password to the password entry field, and clicks the "login." At this time, the user terminal 5-k supplies the ID entered to the ID entry field and the password entered to the password entry field to the database management server 3.

The database management server 3 performs authentication of ID and password supplied from the user terminal 5-k (step S21 in FIG. 3).

The database management server 3 determines whether or not ID and password supplied from the user terminal 5-k are stored to the

freight tracking information database to be associated with each other. When determining that ID and password are not stored in the freight tracking information database (they are not authenticated), the database management server 3 notifies the user terminal 5-k that the use of database is rejected. In response to this notification, the user terminal 5-k displays a message indicating that the use of database is rejected.

On the other hand, when determining that ID and password are stored in the freight tracking information database (they are authenticated), the database management server 3 reads data (data of (c4)), which is associated with the authenticated ID and password and which indicates that the authorization group to which the user belongs. Then, the database management server 3 determines the authentication group indicated by the read data of (c4) (step S22).

Next, the database management server 3 causes the user terminal 5-k to display a selective image for deciding a display image (step S23). The selective image includes a plurality of link destination names to which hyperlinks are added as illustrated in FIG. 5. These link destination names are associated with any of the respective items including, for example, "order", "shipment", "storage", "out of storage", "NVOCC (transportation company using overseas shipping)", and "documents."

Among these items, the link destination name associated with the "order" includes, for example, "P/O and allocation information", "order status information" and "mortgage information."

In the link destination name, "P/O and allocation information", there is provided a hyperlink for displaying an allocation information search image to be described later. In the link destination name, "order status information", there is provided a hyperlink for displaying an order status search image to be described later. In the link destination name, "mortgage information", there is provided a hyperlink for displaying mortgage search image to be described later.

The link destination name associated with the "shipment" includes, for example, "invoice information."

10 In the link destination name "Invoice information", there is provided a hyperlink for displaying invoice information search image to be described later.

The link destination name associated with the "storage" includes, for example, "stock information."

15 In the link destination name "stock information", there is provided a hyperlink for displaying stock search image to be described later.

The link destination name associated with the "out of storage" includes, for example, "goods number information" and "CLP information."

20 In the link destination name "goods number information", there is provided a hyperlink for displaying goods number search image to be described later. In the link destination name "CLP information", there is provided a hyperlink for displaying CLP search image to be described later.

25

10020932-121901

The link destination name associated with the “NVOCC business” includes, for example, “shipping advice information” and “CFM information.”

In the link destination name “shipping advice information”, there  
5 is provided a hyperlink for displaying shipping advice search image to be described later. In the link destination name “CFM information”, there is provided a hyperlink for displaying CFM search image to be described later.

The link destination name associated with the “document”  
10 includes, for example, “customs document”, “overseas shipment document” and “combined transport document.”

In the link destination name “customs document”, there is provided a hyperlink for displaying customs document link image to be described later. In the link destination name “overseas shipment  
15 document”, there is provided a hyperlink for displaying overseas shipment document link image to be described later. In the link destination name “combined transport document”, there is provided a hyperlink for displaying combined transport document link image to be described later.

20 Then, when the user operates the input device of the user terminal 5-k and clicks any of link destination names, the user terminal 5-k supplies information indicating the clicked link destination name to the database management server 3. The database management server 3 decides whether or not the user terminal 5-k is caused to display the  
25 corresponding image depending on which image the link destination

10020932-121901

name indicated by this information is associated with (step S24). In the case where the database management server 3 decides that the user terminal 5-k is caused to display the corresponding image, the image that complies with the operation done by the operator is displayed on  
5 the display screen page of the display device of the user terminal 5-k (step S25).

For example, in the case where the clicked link destination name is "P/O and allocation information", the database management server 3 determines whether or not the authorization group determined in step  
10 S22 is a combined transport cooperation company user (H). Namely, this is because the combined transport cooperation company user (H) is a person who is authorized to gain access to data relating to the combined transport document, and only user authorization group (H) has no authorization to gain access to P/O and allocation information.

15 When determining that the authorization group is (H), the database management server 3 decides that no display of allocation information display image is performed, and causes the user terminal 5-k to display the selective image.

On the other hand, when determining that the authorization group  
20 is not (H), the database management server 3 generates data indicating an allocation information search image and causes the user terminal 5-k to display the allocation information search image.

The allocation information search image has a search key entry field, serving as a search key, for inputting a month on which goods are  
25 shipped and a search button for instructing the database management

10020932-121901

server 3 to start the search.

For example, the user operates the input device of user terminal 5-k, inputs the month on which goods are shipped to the search key entry field of allocation information search image and clicks the search  
5 button. At this time, the user terminal 5-k supplies data indicating the month input to the search key entry field to the database management server 3 and instructs the database management server 3 to perform the search.

The database management server 3 that has received this  
10 instruction searches the freight tracking information database and specifies the day, which belongs to the month supplied from the user terminal 5-k, as a scheduled date for sailing among data of (b41). Then, the database management server 3 reads data of (b1), (b3) and (b4) associated with specified data of (b41). After that, the database  
15 management server 3 generates data representing the allocation information display image in which read data is listed every data associated with the same data of (b41), and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the allocation information display image (for example, image illustrated in FIG. 6)  
20 indicated by this data.

In this case, if the user authorization group is a consignor user (F), the following point is not added as data to be listed. Namely, the point is that data of (b45) associated with the corresponding data does not indicate the authenticated user (user indicated by data of (c1)  
25 associated with authenticated ID) in specified data of (b41) and data

10020932-121901

associated with this data. This is because the consignor user is a person, who is authorized to gain access to data relating to goods of which the user oneself is the consignee.

Moreover, if the authorization group of the authenticated user is a client user (G), the following point is not added as data to be listed. Namely, the point is that data of (b3) associated with the corresponding data does not indicate the authenticated user in specified data of (b41) and data associated with this data. This is because the client user is a person, who is authorized to gain access to data relating to goods of which the user oneself is the consignor.

Additionally, the allocation information display image further includes an item information display button, which is brought into a one-to-one correspondence with listed data of (b1), and an allocation display button, which is brought into a one-to-one correspondence with listed data of (b1) as illustrated in FIG. 6.

Regarding data that represents the allocation information display image, for example, data that describes the corresponding allocation information display image in HTML (HyperText Markup Language) may be used.

Then, when the user operates the input device of user terminal 5-k and clicks the item information display button, the user terminal 5-k supplies data, indicating with which one of data of (b1) the clicked item information display button is associated, to the database management server 3.

The database management server 3 to which this data has been

supplied reads data of (b19), (b12), (b14) to (b17) and (b2). After that, the database management server 3 generates data representing the image in which read data is listed every data about the same data, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the image indicated by this data.

Moreover, when the user operates the input device of user terminal 5-k and clicks the allocation display button, the user terminal 5-k supplies data, indicating with which one of data of (b1) the clicked allocation display button is associated, to the database management server 3.

The database management server 3 to which this data has been supplied reads data of (b5) and (b45) associated with data of (b1) indicated by this data. After that, the database management server 3 generates data representing the image in which read data is listed every data about the same S/O, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the image indicated by this data. Additionally, this image includes an item information display button by S/O, which is brought into a one-to-one correspondence with listed data of (b5).

Then, when the user operates the input device of user terminal 5-k and clicks the item information display button by S/O, the user terminal 5-k supplies data, indicating with which one of data of (b5) the clicked item information display button by S/O is associated, to the database management server 3.

The database management server 3 to which this data has been

10020932-121904



supplied reads data of (b13) to (b17) and (b19) associated with data of (b5) indicated by this data. After that, the database management server 3 generates data representing the image in which read data is listed every data about the same goods, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the image indicated by this data.

In the case where the clicked link destination name is "order status information", the database management server 3 determines whether or not the authorization group to which the authenticated user belongs is a combined transport cooperation company user (H), similar to the case in which the clicked link destination name is "P/O and allocation information."

When determining that the authorization group is (H), the database management server 3 decides that no display of order status display image is performed, and causes the user terminal 5-k to display the selective image.

On the other hand, when determining that the authorization group is not (H), the database management server 3 generates data indicating an order status search image and causes the user terminal 5-k to display the order status search image.

The order status search image has a search key entry field, serving as a search key, for inputting a month on which goods are shipped and a search button for instructing the database management server 3 to start the search.

Then, the user operates the input device of user terminal 5-k,

10020932-121901  
FOI b7E b7C b7D

inputs the month on which goods are shipped to the search key entry field of the order status search image and clicks the search button. At this time, the user terminal 5-k supplies data indicating the month input to the search key entry field to the database management server 3 and instructs the database management server 3 to perform the search.

The database management server 3 that has received this instruction searches the freight tracking information database and specifies the day, which belongs to the month supplied from the user terminal 5-k, as a scheduled date for sailing among data of (b41). Then, the database management server 3 reads data of (b1), (b3), (b4) and (b45) associated with specified data of (b41). After that, the database management server 3 generates data representing the order status search display image in which read data is listed every data associated with the same data of (b41), and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the order status search display image indicated by this data. Additionally, the order status search display image includes a shipping information display button, which is brought into a one-to-one correspondence with listed data of (b1).

In this case, if the authorization group of the authenticated user is (F), the following point is not added as data to be listed. Namely, the point is that data of (b45) associated with the corresponding data does not indicate the authenticated user in specified data of (b41) and data associated with this data.

Moreover, if the authorization group of the authenticated user is

10020932-121901

(G), the following point is not added as data to be listed. Namely, the point is that data of (b3) associated with the corresponding data does not indicate the authenticated user in specified data of (b41) and data associated with this data.

5        Then, when the user operates the input device of user terminal 5-k and clicks the shipping information display button, the user terminal 5-k supplies data, indicating with which one of data of (b1) the clicked shipping information display button is associated, to the database management server 3.

10       The database management server 3 to which this data has been supplied reads data of (b7) to (b11) associated with data of (b1) indicated by this data. After that, the database management server 3 generates data representing the image in which read data is listed every data about the same S/I, and supplies generated data to the user  
15 terminal 5-k. The user terminal 5-k displays the image indicated by this data. Additionally, this image includes an order status display button by S/I, which is brought into a one-to-one correspondence with listed data of (b7).

      Then, when the user operates the input device of user terminal 5-  
20 k and clicks the order status display button by S/I, the user terminal 5-k supplies data, indicating with which one of data of (b7) the clicked order status display button by S/I is associated, to the database management server 3.

      The database management server 3 to which this data has been  
25 supplied reads data of (b12), (b14) to (b20) and (b5) associated with

10020932-121901

data of (b7) indicated by this data. After that, the database management server 3 generates data representing the image in which read data is listed every data about the same goods, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the image indicated by this data. Additionally, this image includes an invoice information display button, which is brought into a one-to-one correspondence with listed data of (b20) and a status date display button, which is brought into a one-to-one correspondence with listed data of (b20).

10 When the user operates the input device of user terminal 5-k and clicks the invoice information display button, the user terminal 5-k supplies data, indicating with which one of data of (b20) the clicked invoice information display button is associated, to the database management server 3.

15 The database management server 3 to which this data has been supplied reads data of (b32) to (b44) associated with data of (b20) indicated by this data. After that, the database management server 3 generates data illustrating the status in which information relating to goods specified by data supplied from the user terminal 5-k is  
20 transmitted between the parties concerned based on the dates indicated by read data, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the image indicating this data. FIG. 7 is a view showing this data to be displayed onto the user terminal 5-k.

As illustrated in FIG. 7, the figure representing data includes a  
25 diagram indicating the production plant, a diagram indicating the

10020932-121901  
T0622T-2E602001

physical distribution center, a diagram indicating the business center, a diagram indicating the customs, a diagram indicating NVOCC (or ship owner), a diagram indicating the shipping port, and a diagram indicating the addressee of goods (client).

- 5        Then, for example, if read data of (b32) includes data representing an actual issue date of D/O, this figure further includes an arrow directing from the diagram indicating a production plant to the diagram indicating the business center.

- 10       If read data of (b37) includes data representing an actual start-up date of the customs procedure, this figure further includes an arrow directing from the diagram indicating the physical distribution center to the diagram indicating the customs.

- 15       If read data of (b36) includes data representing an actual end date of carrying to the shipping port, this figure further includes an arrow directing from the diagram indicating the business center to the diagram indicating the physical distribution center.

- 20       If read data of (b38) includes data representing the date which the resultant report of the custom procedure was received, this figure further includes an arrow directing from the diagram indicating the physical distribution center to the diagram indicating NVOCC.

      If read data of (b40) includes data representing the actual shipment work executing date, this figure further includes an arrow directing from the diagram indicating the physical distribution center to the diagram indicating the shipping port.

- 25       If read data of (b43) includes data representing the actual issue

10020932-121901

date of B/L, this figure further includes an arrow directing from the diagram indicating NVOCC to the diagram indicating the business center.

If read data of (b44) includes data representing the actual issue  
5 date of B/L and the like, this figure further includes an arrow directing from the diagram indicating the business center to the diagram indicating the addressee of goods(client).

When the user operates the input device of user terminal 5-k and clicks the status date display button, the user terminal 5-k supplies data,  
10 indicating with which one of data of (b20) the clicked status date display button is associated, to the database management server 3.

The database management server 3 to which this data has been supplied reads data of (b32) to (b44). After that, the database management server 3 generates data representing the image in which  
15 read data is listed, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the image indicated by this data.

In the case where the clicked link destination name is "mortgage information", the database management server 3 determines whether or not the authorization group to which the authenticated user belongs  
20 is a combined transport cooperation company user (H), similar to the case in which the clicked link destination name is "P/O and allocation information." Then, when determining that the authorization group is (H), the database management server 3 decides that no display of mortgage display image is performed, and causes the user terminal 5-  
25 k to display the selective image. On the other hand, when determining

10020932-121901

that the authorization group is not (H), the database management server 3 generates data indicating a mortgage search image and causes the user terminal 5-k to display the mortgage search image.

The mortgage search image has a search key entry field, serving  
5 as a search key, for inputting an EDP code for goods or goods number and a search button for instructing the database management server 3 to start the search.

Then, the user operates the input device of user terminal 5-k,  
inputs the EDP code for goods or goods number and clicks the search  
10 button. At this time, the user terminal 5-k supplies EDP code for goods or goods number input to the search key entry field to the database management server 3 and instructs the database management server 3 to perform the search.

The database management server 3 that has received this  
15 instruction searches the freight tracking information database and specifies data of (b54) (or (b53)) matching the EDP code (or goods number) supplied from the user terminal 5-k. Then, the database management server 3 reads data of (b3), (b4), and (b45) associated with specified data of (b54) (or (b53)). After that, the database  
20 management server 3 generates data representing the mortgage display image in which read data is listed every data associated with the same data of (b1), and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the mortgage display image indicated by this data. Additionally, the mortgage display image includes a detail  
25 display button, which is brought into a one-to-one correspondence

10020932-121901

with listed data of (b3).

In this case, if the authorization group of the authenticated user is (F), the following point is not added as data to be listed. Namely, the point is that data of (b45) associated with the corresponding data (b54) (or (b53)) does not indicate the authenticated user in specified data of (b54) (or (b53)) and data associated with this data.

Moreover, if the authorization group of the authenticated user is (G), the following point is not added as data to be listed. Namely, the point is that data of (b3) associated with the corresponding data (b54) (or (b53)) does not indicate the authenticated user in specified data of (b54) (or (b53)) and data associated with this data.

Then, when the user operates the user terminal 5-k and clicks the detail display button, the user terminal 5-k supplies data, indicating with which one of data of (b3) the clicked detail display button is associated, to the database management server 3.

The database management server 3 to which this data has been supplied reads data of (b1), (b5), (b8), (b45) to (b47) and (b49) to (b51) associated with data of (b3) indicated by this data. After that, the database management server 3 generates data representing the image in which read data is listed, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the image indicated by this data.

In the case where the clicked link destination name is "invoice information", the database management server 3 determines whether or not the authorization group to which the authenticated user belongs

10020932-121901



is a combined transport cooperation company user (H), similar to the case in which the clicked link destination name is "P/O and allocation information." Then, when determining that the authorization group is (H), the database management server 3 decides that no display of

5 invoice information display image is performed, and causes the user terminal 5-k to display the selective image. On the other hand, when determining that the authorization group is not (H), the database management server 3 generates data indicating an invoice information search image and causes the user terminal 5-k to display the invoice

10 information search image.

The invoice information search image has a search key entry field, serving as a search key, for inputting a scheduled date for shipment work and a search button for instructing the database management server 3 to start the search.

15 Then, the user operates the user terminal 5-k, inputs the scheduled date for shipment work into the search entry field of the invoice information search image and clicks the search button. At this time, the user terminal 5-k supplies the scheduled date input into the search key entry field to the database management server 3 and instructs the

20 database management server 3 to perform the search.

The database management server 3 that has received this instruction searches the freight tracking information database and specifies data of (b40) matching the scheduled date for shipment work supplied from the user terminal 5-k. Then, the database management

25 server 3 reads data of (b55) associated with specified data of (b40).

10020932-121901

After that, the database management server 3 generates data representing the invoice information display image mortgage in which read data is listed, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the invoice information display image indicated by this data. Additionally, the invoice information display image includes an invoice detail display button, which is brought into a one-to-one correspondence with listed data of (b55).

Then, when the user operates the user terminal 5-k and clicks the detail display button, the user terminal 5-k supplies data, indicating with which one of data of (b55) the clicked detail display button is associated, to the database management server 3.

The database management server 3 to which this data has been supplied reads data of (b56) associated with data of (b55) indicated by this data. After that, the database management server 3 generates data representing the image in which read data is displayed, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the image indicated by this data.

In the case where the clicked link destination name is "stock information", the database management server 3 determines whether or not the authorization group to which the authenticated user belongs is a combined transport cooperation company user (H). Then, when determining that the authorization group is (H), the database management server 3 decides that no display of stock display image is performed, and causes the user terminal 5-k to display the selective image. On the other hand, when determining that the authorization

10020932-121901

group is not (H), the database management server 3 generates data indicating a stock search image and causes the user terminal 5-k to display the stock search image.

The stock search image has a search key entry field, serving as a search key, for inputting a month when the user wishes to know the stock quantity of goods and a search button for instructing the database management server 3 to start the search.

Then, the user operates the input device of the user terminal 5-k, inputs the month when the user wishes to know the stock quantity of goods into the search key input field of stock search image and clicks the search button. At this time, the user terminal 5-k supplies data representing the month input into the search key entry field to the database management server 3 and instructs the database management server 3 to perform the search.

The database management server 3 that has received this instruction searches the freight tracking information database and specifies data of (d3) matching the month supplied from the user terminal 5-k. Then, the database management server 3 reads specified data of (d3) and data of (d1) and (d3) associated with this data. After that, the database management server 3 generates data representing a stock display image in which read data is listed every data about the same goods, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the stock display image (for example, an image illustrated in FIG. 8) indicated by this data.

In the case where the clicked link destination name is “goods

number information”, the database management server 3 determines whether or not the authorization group to which the authenticated user belongs is a combined transport cooperation company user (H). Then, when determining that the authorization group is (H), the database  
 5 management server 3 decides that no display of goods number display image is performed, and causes the user terminal 5-k to display the selective image. On the other hand, when determining that the authorization group is not (H), the database management server 3 generates data indicating a goods number search image and causes the  
 10 user terminal 5-k to display the goods number search image.

The goods number search image has a search key entry field, serving as a search key, for inputting a search condition of goods number (for example, range of value where the goods number takes) and a search button for instructing the database management server 3  
 15 to start the search.

Then, the user operates the input device of the user terminal 5-k, inputs the search condition into the search key input field of goods search image and clicks the search button. At this time, the user terminal 5-k supplies data representing the search condition into the  
 20 search key entry field to the database management server 3 and instructs the database management server 3 to perform the search.

The database management server 3 that has received this instruction searches the freight tracking information database and specifies data of (d18) matching the search condition supplied from  
 25 the user terminal 5-k. Then, the database management server 3 reads

specified data of (b18) and data of (b12), (b20), (b22) and (b43) associated with this data. After that, the database management server 3 generates data representing a goods number display image in which read data is listed every data about the same goods, and supplies  
5 generated data to the user terminal 5-k. The user terminal 5-k displays the goods number display image indicated by this data.

In the case where the clicked link destination name is "CLP information", the database management server 3 determines whether or not the authorization group to which the authenticated user belongs  
10 is a combined transport cooperation company user (H). Then, when determining that the authorization group is (H), the database management server 3 decides that no display of CLP display image is performed, and causes the user terminal 5-k to display the selective image. On the other hand, when determining that the authorization  
15 group is not (H), the database management server 3 generates data indicating a CLP search image and causes the user terminal 5-k to display the CLP search image.

The CLP search image has a search key entry field, serving as a search key, for inputting a range of value where the sailing date of a  
20 container takes and a search button for instructing the database management server 3 to start the search.

Then, the user operates the input device of the user terminal 5-k, inputs the search condition into the search key input field of CLP search image and clicks the search button. At this time, the user  
25 terminal 5-k supplies data representing the search condition into the

10020932-121901

search key entry field to the database management server 3 and instructs the database management server 3 to perform the search.

The database management server 3 that has received this instruction searches the freight tracking information database and specifies data of (b41) matching the search condition supplied from the user terminal 5-k. Then, the database management server 3 reads specified data of (b41) and data of (b8), (b20), and (b22) to (b24) associated with this data. After that, the database management server 3 generates data representing a CLP display image in which read data is listed every data about the same goods, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the CLP display image indicated by this data. Additionally, the CLP display image includes a display button by case, which is brought into a one-to-one correspondence with listed data of (b22).

In this case, if the authorization group of the authenticated user is (F), the following point is not added as data to be listed. Namely, the point is that data of (b45) associated with the corresponding data does not indicate the authenticated user in specified data of (b41) and data associated with this data.

Moreover, if the authorization group of the authenticated user is (G), the following point is not added as data to be listed. Namely, the point is that data of (b3) associated with the corresponding data does not indicate the authenticated user in specified data of (b41) and data associated with this data.

Then, when the user operates the user terminal 5-k and clicks the

10020932-121901

display button by case, the user terminal 5-k supplies data, indicating with which one of data of (b20) the clicked display button by case is associated, to the database management server 3.

The database management server 3 to which this data has been  
5 supplied reads data of (b25) to (b27) associated with data of (b22) indicated by this data. After that, the database management server 3 generates data representing the image in which read data is listed every data about the same case, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the image indicated by  
10 this data.

In the case where the clicked link destination name is "Shipping Advice information", the database management server 3 determines whether or not the authorization group to which the authenticated user belongs is a combined transport cooperation company user (H). Then,  
15 when determining that the authorization group is (H), the database management server 3 decides that no display of shipping advice information display image is performed, and causes the user terminal 5-k to display the selective image. On the other hand, when determining that the authorization group is not (H), the database  
20 management server 3 generates data indicating a shipping advice information search image and causes the user terminal 5-k to display the CLP search image.

The shipping advice information search image has a search key entry field, serving as a search key, for inputting a range of issue date  
25 of B/L and a search button for instructing the database management

10020932-121901

server 3 to start the search.

Then, the user operates the user terminal 5-k, inputs the range of issue date of BL into the search key input field of shipping advice information search image and clicks the search button. At this time, 5 the user terminal 5-k supplies data representing the search condition into the search key entry field to the database management server 3 and instructs the database management server 3 to perform the search.

The database management server 3 that has received this instruction searches the freight tracking information database and 10 specifies data of (b43) in which the issue date of B/L is included in the range indicated by data supplied from the user terminal 5-k. Then, the database management server 3 reads specified data of (b28), (b8), (b13), (b46) and (b40) associated with specified data of (b43). After that, the database management server 3 generates data representing a 15 shipping advice information display image in which read data is listed every data about the same B/L, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the shipping advice information display image indicated by this data.

Additionally, the shipping advice information display image 20 includes a B/L detail display button, which is brought into a one-to-one correspondence with listed data of (b28), and a shipping advice detail display button, which is brought into a one-to-one correspondence with listed data of (b28).

In this case, if the authorization group of the authenticated user is 25 (F), the following point is not added as data to be listed. Namely, the

10020932-121901



point is that data of (b45) associated with the corresponding data does not indicate the authenticated user in specified data of (b43) and data associated with this data.

Moreover, if the authorization group of the authenticated user is  
5 (G), the following point is not added as data to be listed. Namely, the point is that data of (b3) associated with the corresponding data does not indicate the authenticated user in specified data of (b43) and data associated with this data.

Then, when the user operates the user terminal 5-k and clicks the  
10 B/L detail display button, the user terminal 5-k supplies data, indicating with which one of data of (b28) the clicked B/L detail display button is associated, to the database management server 3.

The database management server 3 to which this data has been supplied reads data of (b29) associated with data of (b28) indicated by  
15 this data. After that, the database management server 3 generates data representing the image that displays read data, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the image indicated by this data.

Then, when the user operates the user terminal 5-k and clicks the  
20 shipping advice detail display button, the user terminal 5-k supplies data, indicating with which one of data of (b28) the clicked the shipping advice detail display button is associated, to the database management server 3.

The database management server 3 to which this data has been  
25 supplied reads data of (b31) associated with data of (b28) indicated by

10020932-121901

this data. After that, the database management server 3 generates data representing the image that displays read data, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the image indicated by this data.

- 5        In the case where the clicked link destination name is "CFM information", the database management server 3 determines whether or not the authorization group to which the authenticated user belongs is a combined transport cooperation company user (H). Then, when determining that the authorization group is (H), the database
- 10   management server 3 decides that no display of CFM display image is performed, and causes the user terminal 5-k to display the selective image. On the other hand, when determining that the authorization group is not (H), the database management server 3 generates data indicating a CFM search image and causes the user terminal 5-k to
- 15   display the CFM search image.

The CFM search image has a search key entry field, serving as a search key, for inputting a search condition of CFM (a range of value where date of arrival in port of a container takes) and a search button for instructing the database management server 3 to start the search.

- 20        Then, the user operates the input device of user terminal 5-k, inputs the search condition into the search key input field of CFM search image and clicks the search button. At this time, the user terminal 5-k supplies data representing the search condition into the search key entry field to the database management server 3 and
- 25   instructs the database management server 3 to perform the search.

106727-25602001

The database management server 3 that has received this instruction searches the freight tracking information database and specifies data of (b42) matching the search condition supplied from the user terminal 5-k. Then, the database management server 3 reads 5 specified data of (b42), and data of (b22), (b41) and (b43) associated with this data. After that, the database management server 3 generates data representing a CFM display image in which read data is listed every data about the same container, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the CFM display 10 image indicated by this data. Additionally, the CFM display image includes a display button by case, which is brought into a one-to-one correspondence with listed data of (b22).

In this case, if the authorization group of the authenticated user is (F), the following point is not added as data to be listed. Namely, the 15 point is that data of (b45) associated with the corresponding data does not indicate the authenticated user in specified data of (b42) and data associated with this data.

Moreover, if the authorization group of the authenticated user is (G), the following point is not added as data to be listed. Namely, the 20 point is that data of (b3) associated with the corresponding data does not indicate the authenticated user in specified data of (b42) and data associated with this data.

Then, when the user operates the user terminal 5-k and clicks the display button by case, the user terminal 5-k supplies data, indicating 25 with which one of data of (b22) the clicked display button by case is

associated, to the database management server 3.

The database management server 3 to which this data has been supplied reads data of (b25) to (b27) associated with data of (b22) indicated by this data and data of (b5). After that, the database  
5 management server 3 generates data representing the image in which read data is listed every data about the case, and supplies generated data to the user terminal 5-k. The user terminal 5-k displays the image indicated by this data.

In the case where the clicked link destination name is “customs  
10 document”, the database management server 3 determines whether or not the authorization group to which the authenticated user belongs is an in-company general user (E). Then, when determining that the authorization group is (E), the database management server 3 decides that no display of customs document display image is performed, and  
15 causes the user terminal 5-k to display the selective image. On the other hand, when determining that the authorization group is not (E), the database management server 3 generates data representing a customs document link image and causes the user terminal 5-k to display the customs document link image.

20 The customs document link image is an image that lists the names of the foregoing data (a8), and a hyperlink to data of (a8) having the corresponding name is provided to each name.

In the case where the clicked link destination name is “overseas shipment document”, the database management server 3 determines  
25 whether the authorization group to which the authenticated user

10020932.121901  
FO6T2T 2E602001

belongs is a combined transport business user (D) or an in-company general user (E). Then, when determining that the authorization group is (D) or (E), the database management server 3 decides that no display of overseas shipment document display image is performed, and

5 causes the user terminal 5-k to display the selective image. On the other hand, when determining that the authorization group is neither (D) nor (E), the database management server 3 generates data representing an overseas shipment document link image and causes the user terminal 5-k to display the overseas shipment document link  
10 image.

The overseas shipment document link image is an image that lists the names of the foregoing data (a1) or (a4), and a hyperlink to data of (a1) or (a4) having the corresponding name is provided to each name.

In the case where the clicked link destination name is “combined  
15 transport document”, the database management server 3 determines whether the authorization group to which the authenticated user belongs is an export business user (C) or an in-company general user (E). Then, when determining that the authorization group is (C) or (E), the database management server 3 decides that no display of combined  
20 transport document display image is performed, and causes the user terminal 5-k to display the selective image. On the other hand, when determining that the authorization group is neither (C) nor (E), the database management server 3 generates data representing a combined transport document link image and causes the user terminal 5-k to  
25 display the combined transport document link image.

The combined transport document link image is an image that lists the names of the foregoing data (a2), (a3), (a5) to (a7) and (a9) to (a15), and a hyperlink to data of (a2), (a3), (a5) to (a7) and (a9) to (a15) each having the corresponding name is provided to each name.

5 It should be noted that the structure of the freight tracking information management system is not limited to the aforementioned case.

For example, the same server computer may perform the functions of the database management server 3 and the key business  
10 server 1-j, and the user terminal 5-k may perform the functions of the database management terminal 4. Also, the key business terminal 2-j may perform the functions of the database management terminal 4. Moreover, the scanner S may be connected to the key business terminal 2-j.

15 Still moreover, this freight tracking information management system may be used to perform the registration of data of the document relating to the import procedure of goods, the search thereof, or the viewing thereof.

Still moreover, this freight tracking information management  
20 system may provide an electronic watermark or a digital signature to PDF-formatted image data generated by this system. The provision of the electronic watermark or the digital signature to PDF-formatted image data prevents this image data from being tampered more reliably.

25 However, even if image data representing the document is

10020932-121901

10020932-121901

tampered, there is no occurrence in which the description matters of the document are illegally changed since image data is not the original of the document. There is a method in which image data is used in place of the original in advancing the procedures of imports and  
5 exports. Accordingly, this method itself can also play a role in preventing the danger that the original is tampered in the process in which the procedure advances.

There is a contract in which the PDF-formatted image data that is generated by this freight tracking information management system is  
10 handled as substantially identical with the original of the document representing the corresponding image data. This contract may be concluded between the users of the freight tracking information management system. Moreover, there is a contract in which the manager of the freight tracking information management system  
15 guarantees the identity of the description contents represented by the corresponding PDF-formatted image data and those of the original of the document represented by the corresponding image data. This contract may be concluded between the manager of the freight tracking information management system and the user.

20 Though the above explained the embodiment of the present invention, the physical distribution management system according to the present invention may be implemented using the general computer system instead of the dedicated system.

For example, from a storage medium (CD-ROM, magnetic tape,  
25 and the like) that stores the programs for executing the operations of

the foregoing key business server 1-j, key business terminal 2-j, database management server 3, database management terminal 4 and user terminal 5-j, the corresponding program is installed on a plurality of computers each having DSU and a terminal adopter and connected to each other. This makes it possible to construct the freight tracking information management system that executes the aforementioned processing.

Moreover, for example, the corresponding program of a communications line is posted on a bulletin board system (BBS) and this may be distributed via the communications line. Still moreover, a carrier wave is modulated by a signal representing the corresponding program and an obtained modulation wave is transmitted. Then, the device that has received this modulation wave may demodulate the modulation wave to restore the corresponding program.

After that, this program is started up and executes it under control of OS, similar to the other application programs, making it possible to execute the aforementioned processing.

Additionally, in the case where OS shares a part of processing or OS constitutes a part of one component of the present invention, a program excluding such a part may be stored to a storage medium. In this case, according to the present invention, it is assumed that programs for executing the programs that execute the respective functions executed by the computer or the steps are stored in the storage medium.

As explained above, according to the present invention, there can



be implemented a physical distribution business management method that makes it easy to grasp the progress of the procedure relating to the transport of goods, and a physical distribution business management system.

- 5        Various embodiments and changes may be made thereunto without departing from the broad spirit and scope of the invention. The above-described embodiment is intended to illustrate the present invention, not to limit the scope of the present invention. The scope of the present invention is shown by the attached claims rather than the
- 10    embodiment. Various modifications made within the meaning of an equivalent of the claims of the invention and within the claims are to be regarded to be in the scope of the present invention.

- This application is based on Japanese Patent Application No. 2000-387958 filed on December 20, 2000 and including specification,
- 15    claims, drawings and summary. The disclosure of the above Japanese Patent Application is incorporated herein by reference in its entirety.

10020932-121901